



SERIES 120-2

1-1/2" TO 2" DEFLECTION SPRING ISOLATORS

CATALOG NO. 91A-756-C



121-2

122-2

124-2

Superior Isolation Efficiency: Series "120-2" spring isolator provides static deflection from 1-1/2" to 2". As a result, it eliminates bolting of equipment to floor in many applications, improves working conditions, reduces building and machine maintenance.

Lateral Stability: Elastomer cushioned housing provides damping and controls excessive horizontal movement.

Safe and Compact: All welded steel housing assures strength and weight saving advantages.

East to Install: Built-in leveling bolt eliminates shimming in all applications, and saves installation cost.

Effective Noise Reduction: The elastomeric pad effectively interrupts structure-borne noise transmission paths to prevent noise amplifications caused by sounding-board effect.

Applications: The high deflection spring isolators are required for roof top, upper floor, hospital, and some laboratory installations

STATIC DEFLECTIONS (IN INCHES)	ISOLATION EFFICIENCY		
	900 cpm	1200 cpm	1800 cpm
1.50	97.0%	98.4%	99.3%
1.75	97.5	98.6	99.4
2.00	97.8	98.8	99.5

ACE MOUNTINGS CO., INC.

11 Cross Avenue
South Amboy, NJ 08879
Tel: (732)721-6200 Fax: (732)721-5005
Email: acemount@att.net
Website: www.acemount.com